

Switch Mode Power Supply

ATX12V v.1.3~ 12 cm fan - Active PFC -



Dimension: L150 x W140 x H86mm
(5.9" x 5.5" x 3.4")

Features

- Specification compliance: ATX12V v1.3 & AMD Athlon
- Pentium 4 ready with P4 connectors
- Forward converter circuit
- High efficiency and reliability
- Low ripple & noise
- Super low noise fan control
- Short circuit protection on all outputs
- Over voltage protection
- Over power protection
- 100% hi-pot test
- 100% burn in, high temperature cycled on/off

DC Output & Features

Model	DC output					Total power	Input voltage	
	+3.3V	+5V	+12V	-12V	+5Vsb		Full range	Fixed 220V
SS-300FT Active PFC	28A	30A	18A	0.8A	2A	300W	Yes	Yes
	200W(46A) ¹							
SS-350FT Active PFC	28A	30A	19A	0.8A	2A	350W	Yes	Yes
	200W(46A) ¹							
SS-400FT Active PFC	28A	30A	22A	0.8A	2A	400W	Yes	---
	200W(46A) ¹							

Remarks: 1. Combined +3.3VDC & +5V DC maximum power

specification may change without prior notice

Electrical Specification

Input frequency:	50/60Hz
In-rush current, cold start:	80A max.
Hold up time, full load:	16ms. typical
Efficiency:	at normal input voltage >70%
	at AC 115v 60Hz 74% typical
	at AC 230v 50Hz 77% typical
Dielectric withstand, input to frame/ground:	1800VAC, 1sec.
Dielectric withstand, input to output:	1800VAC, 1sec.
Line regulation:	'+/- 1% typical
Load regulation:	'+/- 5% typical
Cross regulation:	'+/- 5% typical
Ripple / noise:	1%
MTBF, full load @ 25°C amb. Excluding the DC fan:	>100k hrs
Power Factor Correction: Active PFC	99% typical

Sea Sonic Electronics Co., Ltd.

Head Office:

8th Fl., #19 Alley 360, Sec. 1, Neihu Road,
Neihu, Taipei, Taiwan, R.O.C.

Tel: +886 2 2659 0338

Fax: +886 2 2659 0530

sales@seasonic.com.tw

www.seasonic.com

Factories:

I. Tao Yuan, Taiwan.

II. Dong Guan, China.

Europe office:

tel: +31 73 644 9288

fax: +31 73 511 2217

netherlands@seasonic.com

USA office:

tel: +1 626 969 9966

fax: +1 626 969 9986

usa@seasonic.com

Safety compliance



EMI/RFI compliance

